REPORT SS-H SYSTEM MONTHLY LOADS SUMMARY

This report gives monthly values of electrical energy for fans, gas/oil energy for heating and cooling, and electrical energy for heating and cooling for an HVAC system. The name of the system (SYST-1) is shown in the title.

FAN ELEC

shows the total and maximum hourly electrical consumption of the supply, return, exhaust, and zonal fans.

2. FUEL HEAT

shows the total oil and gas consumption by packaged systems for heating, in Btuequivalents. This will be zero unless you have made at least one of the heat sources FUR-NACE.

3. FUEL COOL

shows the total oil and gas consumption by packaged systems for cooling, in Btu-equivalents.

4. ELEC HEAT

shows the electrical consumption for heating. This will include electric baseboards and reheat coils as well as the electrical load attributable to the heating cycle of a heat pump.

5. ELEC COOL

shows the electrical consumption and hourly maxima for cooling.

SIMPLE STRUCTURE RUN 3, CHICAGO DIVIDE INTO ZONES; ADD PLENUM DOE-2.1E-001 Thu Nov 4 15:19:02 1993SDL RUN 1
DESIGN-DAY SIZING OF VAV SYSTEM SHOW ALL REPORTS
REPORT- SS-H SYSTEM MONTHLY LOADS SUMMARY FOR SYST-1 WEATHER FILE- TRY CHICAGO

DIVIDE INTO ZONES: ADD PLENUM

	FAN B	L E C	FUEL	H B A T	FUEL	C O O L	-E L E C	H E A T	-E L E.C	C O O L
	FAN ENERGY	HAXINUM FAN LOAD	GAS OIL ENERGY	MAXIMUM GAS OIL LOAD	GAS OIL ENERGY	MAXIMUM GAS OIL LOAD	ELECTRIC ENERGY	NAX INUM ELECTRIC LOAD	ELECTRIC ENERGY	MAXIMUM ELECTRIC LOAD
HONTH		(KM)	(HBTU)	(KBTU/HR)	(MBTU)	(KBTU/HR)	(1044)	(ICM)	(IO/H)	(KDF)
										0.000
JAN	256.	3.984	0.000	0.000	0.000	0.000	0.	0.000	0.	0.000
FEB	215.	3.070	0.000	0.000	. 0.000	0.000	0.	0.000	0.	0.000
MAR	195.	3.320	0.000	0.000	0.000	0.000	0.	0.000	٥.	0.000
APR	182.	2.198	0.000	0.000	0.000	0.000	0.	0.000	0.	0.000
HAY	263.	2.955	0.000	0.000	0.000	0.000	٥.	0.000	0.	0.000
JUN	469.	4.156	0.000	0.000	0.000	0.000	0.	0.000	0.	0.000
JUL	758.	7.304	0.000	0.000	0.000	0.000	0.	0.000	0.	0.000
ADG	724.	5.987	0.000	0.000	0.000	0.000	0.	0.000	٥.	0.000
SEP	346.	4.123	0.000-	0.000	0.000	0.000	0.	0.000	0.	0.000
OCT	173.	1.794	0.000	0.000	0.000	0.000	0.	0.000	0.	0.000
NOV	171.	3.021	0.000	0.000	0.000	0.000	0.	0.000	0.	0.000
DEC	231.	3.543	0.000	0.000	0.000	0.000	0.	0.000	0.	0.000
. TOTAL	L 4181.		0.000	7	0.000		0.		0.	
· KAX	18450	7.304		0.000		0.000		0.000		0.000

REPORT SS-L FAN ELECTRIC ENERGY FOR <system>

This report gives a breakdown of monthly electric energy for fans (central and zone-level) and fan part load operation for an HVAC system.

The energy quantities on the left-hand side of the report are given for heating hours only, cooling hours only, simultaneous heating and cooling hours, and floating hours.

- FAN ELECTRIC ENERGY DURING HEATING gives the total electric energy used by the fans in all hours when only heating is required.
- FAN ELECTRIC ENERGY DURING COOLING gives the total electric energy used by the fans in all hours when only cooling is required.
- FAN ELECTRIC ENERGY DURING HEATING-COOLING
 gives the total electric energy used by the fans in all hours when both heating and cooling
 are required.
- 4. FAN ELECTRIC ENERGY DURING FLOATING gives the total electric energy used by the fans when neither heating nor cooling is provided.

The right-hand side of the report shows the part-load operation of the fans. The number of operating hours within each percentage part load band (0-10%, 0-20%, etc.) is given as well as the total hours of operation. If the fan operates during an hour, its part load in percent is determined as 100*(total flow)/(design SUPPLY-CFM).

SIMPLE STRUCTURE RUN 3, CHICAGO ESIGN-DAY SIZING OF VAV SYSTEM EPORT- SS-L FAN ELECTRIC ENERGY DIVIDE INTO ZONES: ADD PLENUN

DOE-2.1E-001 Thu Hov 4 15:19:02 1993SDL RUN 1

SHOW ALL REPORTS

SYST-1

WEATHER FILE- TRY CHICAGO

	FAN ELEC	FAN ELEC	FAN ELEC	FAN ELEC		N	umber	of hou	rs with	nin eac	h PART	LOAD	range			TOTAL
	DURING HEATING	DURING	DURING HEAT & COOL	DURING FLOATING	10	10	20 30	30 40	40 50	60	70	70 80	90	100	100	HOURS
HTMON	(KMH)	(HMH)	(KMH)	(KWK)												•
														14		
JAN	256.361	0.000	0.000	0.000	0	0	0	286	10	4	4	1	0	0	0	305
FEB	214.658	0.000	0.000	0.000	0	0	0	239	10	3	3	1	0	0	0	256
MAR	188.892	0.000	0.000	5.833		0	0	242	3	1	2	0	0	0	0	248
APR	77.282	59.311	0.000	45.241	0	0	0	216	11	2	0	0	0	0	0	229
MAY	29.165	172.787	0.000	61.428	. 0		0	144	45	27	4	0	0	0	0	220
JUN	0.000	465.212	0.000	3.377	0	. 0	0	23	49	80	51	4	0	0	0	207
JUL	0.000	957.790		0.000	0	0	0	1	9	35	72	66	29	28	1	241
AUG	0.000	723.851	0.000	0.000	0	0		9	24	62	91	40	12	0	•	238
SEP	9.505	303.856	0.000	32.739	0	0			45	37	32	3	0	0	(205
OCT	63.882	77.672	0.729	31.766	٥	0		224	1	0	0	0	0	0	(225
HOV.	148.524	13.219		8.918	0	0		200	5	2	2	0	0	0		209
DEC	230.728	0.000			0			259	11	0	6	0	0	0		0 276
DEC										••••						
ANNUAL	1218.994	2773.70	3 0.729	189.301	0	, (1931	223	253	267	115	41	28		1 2859

REPORT SS-M FAN ELECTRIC ENERGY FOR PLANT

This report gives a breakdown of fan electric energy for each month passed to PLANT. The quantities are given for heating hours only, cooling hours only, simultaneous heating and cooling hours, and floating hours. The quantities are calculated by summing the individual space quantities.

- FAN ELECTRIC ENERGY DURING HEATING
 gives the total electric energy used by the fans in all hours when only heating is required.
- FAN ELECTRIC ENERGY DURING COOLING gives the total electric energy used by the fans in all hours when only cooling is required.
- FAN ELECTRIC ENERGY DURING HEATING-COOLING
 gives the total electric energy used by the fans in all hours when both heating and cooling
 are required.
- 4. FAN ELECTRIC ENERGY DURING FLOATING gives the total electric energy used by the fans when neither heating nor cooling is provided.

SIMPLE STRUCTURE RUN 3, CHICAGO DIVID DESIGN-DAY SIZING OF VAV SYSTEM SHOW A REPORT- SS-M FAN ELECTRIC ENERGY FOR PLANT

DIVIDE INTO ZONES: ADD PLENUM

SHOW ALL REPORTS

DEFAULT-PLANT

WEATHER FILE- TRY CHICAGO

MONTH	FAN ELECTRIC ENERGY DURING HEATING (KMH)	FAN ELECTRIC ENERGY DURING COOLING (KWH)	FAN ELECTRIC ENERGY DURING HEATING-COOLING (XMH)	PAN ELECTRIC ENERGY DURING FLOATING (KNH)
JAN	256.361	0.000	0.000	0.000
FEB	214.658	0.000	0.000	0.000
KAR	188.892	0.000	0.000	5.833
APR	77.282	59.311	0.000	45.241
KAY	29.165	172.787	0.000	61.428
JUN	0.000	465.212	0.000	3.377
JUL	0.000	957.790	0.000	0.000
AUG	0.000	723.851	0.000	0.000
SEP	9.505	303.856	0.000	32.739
OCT	63.882	77.672	0.729	31.766
NOV	148.524	13.215	0.000	8.918
DEC	230.728	0.000	0.000	0.000
ANNUA	L 1218.994	2773.703	0.729	189.301

REPORT SS-N RELATIVE HUMIDITY SCATTER PLOT

In this scatter plot, the ordinate, appearing in the left column, shows relative humidity bins. The abscissa, shown at the top, gives hours of the day. Entered in each cell of the plot is the number of hours during the RUN-PERIOD for which the relative humidity of the system return air was in the particular relative humidity bin for this particular hour of the day. Only hours for which the fans are on are counted in this plot.

The column at the far right is the sum of the entries in each row. It shows the frequency of relative humidity values for the RUN-PERIOD. (Because the relative humidity counts are made only for hours when the fans are on, summing the totals column will not sum to the number of hours in the run.)

Note: If fans are on due to NIGHT-CYCLE-CTRL, the hours will not be counted in the plot.

SIMPLE STRUCTURE RUN 3, CHICAGO DIVIDE INTO ZONES; ADD PLENUM DOE-2.1E-001 Thu Nov 4 15:19:02 1993SDL RUN 1 DESIGN-DAY SIZING OF VAV SYSTEM SHOW ALL REPORTS REPORT- SS-N RELATIVE HUMIDITY SCATTER PLOT FOR SYST-1 WEATHER FILE- TRY CHICAGO

TOTAL HOURS AT RELATIVE HUMIDITY LEVEL AND TIME OF DAY

HOUR	18	K 2	3	4	5	6	7	8	9	10	11	12	1P9	1 2	3	4			7		9	10	11	12	TOTAL
80-100	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	1
70-80	0	0	0	0	0	0	0	0	1	0	0	0	0	1	0	1	1	0	0	0	0	0	0	0	4
60-70	0	0	0	0	0	0	0	6	5	5	5	4	4	2	2	3	3	3	0	0	0	0	0	0	42
50-60	0	0	0	0	0	0	0	45	58	57	53	32	33	29	28	34	35	4	0	0	0	0	0	0	408
40-50	0	0	0	0	0	0	0	42	43	45	41	60	61	69	66	59	61	9	0	0	0	0	0	0	556
30-40	0	0	0	0	0	0	0	26	62	61	57	49	38	48	52	55	51	27	0	0	0	0	0	0	526
0-30	0	0	0	0	0	0	0	7	83	84	96	107	116	103	103	100	101	83	0	0	0	0	0	0	983
	***		***			***				***			***		***	***	***		***	***	***	***	***	***	*****

REPORT SS-O TEMPERATURE SCATTER PLOT

In this scatter plot, the ordinate, appearing in the left column, shows temperature bins. The abscissa, shown at the top, gives hours of the day. Entered in each cell of the plot is the number of hours during the RUN-PERIOD for which the zone air temperature was in the particular bin for this particular hour of the day. Only hours for which the fans are on are counted in this plot.

The column at the far right is the sum of the entries in each row. It shows the frequency of temperature values for the RUN-PERIOD. (Because the temperature counts are only made for hours when the fans are on, summing the totals column will not sum to the number of hours in the run.)

Note: If fans are on due to NIGHT-CYCLE-CTRL, the hours will not be counted in the plot.

DIVIDE INTO ZONES; ADD PLEMUM

SIMPLE STRUCTURE RUN 3. CHICAGO DIVIDE INTO ZONES; ADD PLEMUN
DESIGN-DAY SIZING OF VAV SYSTEM SHOW ALL REPORTS
REPORT- SS-0 TEMPERATURE SCATTER PLOT SYST-1 FOR SPACE1-1

TOTAL HOURS AT TEMPERATURE LEVEL AND TIME OF DAY

HOUR	18	H 2	1	3	4	5	6	7		9	10	11	12	11	H 2	3	4	5	6	7		9	10	11	12	TOTAL
		•••	•	•••								•						•••								
ABOVE 85	0		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
80-85	0		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
75-80	0		0	0	0	0	0	0		90	96	100	106	119	132	141	144	139	15	0	0	0	0	0	0	1170
70-75	0		0	0	0	0		0	38	162	156	152	145	132	119	110	107	112	110	0	0	0	0	0	0	1343
65-70	0		0	0	0	0	۰	0	0	0	0	•	1	1	1	1	1	1	1	0	0	0	0	0	0	7
60-65	0		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
BELOW 60	0		0	0	0	0	۰	0	0	0	0	0	0	٥	0	0	0	0	0	0	0	0	0	0	0	0